


The aim of this tutorial is to provide you with an introduction to setting up a project according to the CNOSSOS-EU guideline for aircraft noise.




The basis for this project is using the data interface QSI according to DIN 45687. An example is stored in the IMMI installation folder, see Exampleprojects\Aircraft noise. This tutorial is based on the guideline CNOSSOS-EU.




Choose Create new project and confirm with Ok.







In the dialog box Set project properties ...: for the topic choose Aircraft noise and for type of prediction and for the rating method choose CNOSSOS/flight noise (FRG).





Confirm with Ok.






Import Cancel Help








Click on the icon to open the tab for the settings for aircraft noise. The airport reference point and a lot of calculation settings are displayed. Close the dialog box with OK.




For checking the imported take-off and landing runways go to menu Extras I Aircraft noise I Take-off and landing runways. Use Edit ... to open the dialog box of the first entry.









Open the database for elements via menu Project I Elements or use the corresponding icon. In the element library **Aircraft noise** (BUF) you see 3 element types: flight routes, traffic patterns and the helicopter flight routes.




Double-click on the first entry to open the input dialog. All general input data is shown here.




Open the DAS tab by clicking on the button just to see the input data. Close the dialog box with OK.






Back to the database take a look at the other elements – Traffic circuit or helicopter. Use the Close button to exit the database.




In the map, the corridor width of the flight routes can be displayed be using the corresponding button.

IMMI 2019 (C:\Users\dr\Desktop\EDyy\_final\_BUF.IPR)






Choose OpenStreetMap as the background image. Use the Select area button to choose a small area around the airport. Click OK to start the import.





The import dialog box is shown. Activate the buildings and enter 8m for replacement value for building height (m). Click on Search map feature in file. The number of houses are listed.

Click on Import button to import the buildings.





... 22442045 4 ... 5070750 (







Start the receiver point calculation using the corresponding icon. Activate all result list under Quantity of results und click on Calculate to start the calculation. If there are messages, close them and continue the calculation.











Start the grid calculation with the corresponding icon. Define a filename and a folder for the result and activate the multicore function to speed up your calculation. If there are messages, close them and continue the calculation.





IMMI supports 2 databases, the internal and the external one.

- The <u>external databases</u> for aircraft noise (Extras | External Databases | Aircraft Noise) contain all aircraft classes of the different regulations and can be supplemented by additional aircraft classes as required.
- The <u>internal databases</u> (Project | Internal Databases | Aircraft Noise) contain the aircraft classes used in the project or, in a newly created project, the entries from the external databases. The entries from the internal database are always used when editing the project. Additional aircraft classes can be added. **Note**: Deleting aircraft classes from the internal database will move the aircraft classes to the input dialog of the elements. Deleting entries should only be done if the IMMI project does not contain flight routes.

